

FEED OUT TRAILERS & SKID FEEDERS



Smart, Easy
Stockfeeding
Solutions



Grainline[®]

1800 810 498
www.grainline.com.au





BUILT FOR CONFIDENCE ... Grainline Feed Out Trailers are engineered with our unique 'smart design' and deep profile bin construction to ensure maximum strength, durability, simple operation and low maintenance use.

PACKED WITH FEATURES ... Discover our unique blend of features which brings you the 'next generation' multi-function feeders.




Deep profile construction for all round maximum strength, durability & longevity



Zinc coated doors slide in nylon tracks to ensure consistently smooth and jam free operation



Trail feed door activated by manual or remote operation



Sealed reduction gearbox for reliability and zero maintenance for peace of mind



Horizontal bin doors front & rear* operated from front of trailer or optional remote operation available *(4.0 tonne units only)



Trail feed door operated remotely by hand held remote or triple touch brake action

* All models include clean out trap door mechanism

OPTIONAL FEATURES ...



Allows for controlled application of extra nutrients

Controlled grain delivery for precision feeding



SCALES



TROUGH AUGER

Simply switch to trough feeding without removing main auger

Optional registration, subject to state requirements

... maximise your trailer



REGISTRATION



2.5 TONNE (30 BAG) FEED OUT TRAILER
including 3m x 5 inch Auger



4.0 TONNE (50 BAG) FEED OUT TRAILER
including 4m x 6 inch Auger



2.5 TONNE + 4.0 TONNE SKIDS

	DESCRIPTION	FEED OUT TRAILERS		SKID FEEDERS	
		2.5 TONNE	4.0 TONNE	2.5 TONNE	4.0 TONNE
BRAKES	E-brakes (one axle)	Standard	Standard		
TAIL LIGHTS	LED tail lights	Standard	Standard		
DOWNSPOUT	Poly downspout w/ flexi elbow	Standard	Standard	Standard	Standard
TRAIL FEED	Trail feed door w/ remote	Standard	Standard		
TARP	Pull-over tarp w/ bungee straps	Standard		Standard	
TARP	With roll over tarp		Standard		Standard
AUGER SIZE	3m x 5 inch = 2.3m clearance from spigot	Standard		Standard	
AUGER SIZE	4m x 6 inch = 3.1m clearance from spigot		Standard		Standard
BIN LADDER	4 rung ladder	Standard	Standard	Standard	Standard
GFTTROUGH	Trough auger 700mm	Optional	Optional	Optional	Optional
GFTHDA2	Twin actuators on hopper doors		Optional		Optional
GFTAB	Additive Box (Gravity Box)		Optional		Optional
GFTSC	Scales (x320 digital readout)	Optional	Optional	Optional	Optional
GFTBW	Scales upgrade to batch weighing	Optional	Optional	Optional	Optional
GFTEB02	E/brakes on second axle (includes break-away)	Optional	Optional		
GFTOBBC	On-board brake control	Optional	Optional		
GFTREGO	Rego ready with blue slip & VIN number (NB. includes brakes on second axle)	Optional	Optional		

Specifications subject to change without notice

